

Specifications

Casing		Casing ID Size (in.)	Gauge OD of Packer (in.)	Min. ID of Packer (in.)	Thread connection	
Size (in.)	Weight (lbs/ft)					
4-1/2	9.5-13.5	3.910-4.090	3.771	1.995	2-3/8" EUE	
5	15-18	4.250-4.408	4.125			
	11.5-15	4.408-4.560	4.250			
5-1/2	13.0-15.5	4.950-5.190	4.781		2.441	2-3/8" EUE
	15.5-20.0	4.778-4.950	4.641			
	20.0-23.0	4.625-4.778	4.500			
6-5/8	20-24	5.921-6.049	5.661	2.441		2-3/8" & 2-7/8" EUE
	24-28	5.791-5.921	5.625			
	28-32	5.675-5.791	5.484			
7	17.0-20.0	6.456-6.578	6.266	1.995 OR 2.441	2-7/8" & 3-1/2" EUE	
	20.0-26.0	6.276-6.456	6.078			
	26.0-32.0	6.094-6.276	5.968			
	32.0-35.0	5.938-6.135	5.812			
7-5/8	20-24	7.025-7.125	6.812	2.441 OR 2.992	2-7/8" & 3-1/2" EUE	
	24-29.7	6.798-7.025	6.672			
	33.7-39	6.579-6.797	6.453			
9-5/8	40-47	8.681-8.835	8.437	2.992 OR 3.958	3-1/2" & 4-1/2" EUE	
	47-53.5	8.343-8.681	8.281			