

Specifications

Casing			Preferred Casing ID Range		Differential Pressure (psi)	Temperature Rating (°F)	
OD (in.)	Wt T&C (lbs/ft)	Max OD (in.)	Min (in.)	Max (in.)		70 HD	90 HD
4-1/2	9.5-16.6	3.593	3.826	4.090	10,000	up to 225	125 to 400*
5	11.5-20.8	3.937	4.154	4.560			
5-1/2	26.0-32.3						
	14-23	4.312	4.580	5.044			
6	18-26	4.937	5.140	5.552			
7	49.5						
6-5/8	20-32	5.410	5.595	6.135			
7	32-44						
		17-35	5.687	6.000			
7-5/8	45.3						
	20-39	6.312	6.625	7.125			
7-3/4	46.1						
8-5/8	24-49	7.125	7.511	8.097			
8-3/4	49.7						
9-5/8	32.3-58.4	8.125	8.435	9.063	8,000	up to 225	125 to 400*
9-3/4	59.2						
9-7/8	62.8						
10-3/4	60.7-81	9.000	9.250	9.660	5,000	up to 225	125 to 400*
		32.75-60.7	9.437	9.660			
11-3/4	60.0-83.0	9.937	10.19	10.772	4,000	up to 225	125 to 400*
		42-60	10.437	10.77			
13-3/8	85-102	11.562	11.63	12.159	3,000	up to 225	125 to 400*
		48-80.7	12.000	12.17			
13-1/2	81-4						
13-5/8	88.2						
16	109.0-146.0	13.915	14.00	14.750	V150 2500	up to 225	125 to 400*
		55.0-84.0	14.585	14.70	15.400		